

SPJT



Spray angle	60°	90°	120°	150°	170°
-------------	-----	-----	------	------	------

Thread size	Flow code	Spray hole Di.a(mm)	Free passage orifice Dia.(mm)	Flow rate(L/min)				
				0.7bar	1.5bar	3bar	7bar	25bar
1/4"	07	2.4	2.4	2.6	3.9	5.5	8.4	16
	13	3.2	3.2	4.9	7.3	10.3	15.7	30
	20	4.0	3.2	7.6	11.2	15.8	24	46
3/8"	07	2.4	2.4	2.6	3.9	5.5	8.4	16
	13	3.2	3.2	4.9	7.3	10.3	15.7	30
	20	4.0	3.2	7.6	11.2	15.8	24	46
	30	4.8	3.2	11.4	16.7	24	36	68
	40	5.6	3.2	15.1	22	32	48	91
	53	6.4	3.2	20	30	42	64	121
1/2"	82	7.9	3.2	31	46	65	99	187
	120	9.5	4.8	45	67	95	145	270
3/4"	164	11.1	4.8	62	92	129	198	370
	210	12.7	4.8	80	117	166	255	480
1"	340	15.9	6.4	130	190	270	410	775
	470	19.1	6.4	179	260	370	565	1070
1-1/2"	640	22.2	7.9	245	355	505	770	1460
	820	25.4	7.9	310	455	645	990	1870
	960	28.6	7.9	365	535	755	1160	2190
2"	1400	34.9	11.1	535	780	1105	1690	3190
	1780	38.1	11.1	680	995	1405	2150	4060
3"	2560	44.5	14.3	980	1430	2020	3090	5830
	3360	50.8	14.3	1280	1880	2650	4050	7660
4"	5250	63.5	15.9	2000	2930	4140	6330	11960

Ordering Information :

Thread size	Style No.	Material	Spray angle	Flow Code
-------------	-----------	----------	-------------	-----------

Example

1/4"	SPJT	SS	90	30
Thread size	Style No.	Material	spray angle	Flow code